

ER14250M

3.6V Primary Lithium Thionyl Chloride High Power 1/2AA-size Spiral wound

Characteristics

- High energy density
- High and stable operating voltage during most of the lifetime in the application
- Wide range of operating temperature (-55°C~+85°C)
- Long operating time
- Low self-discharge rate (less than 1% after 1 year of storage)
- Long storage life (over 10 years under normal room temperature)

Main Applications

- Utility metering
- Automatic meter reading
- Memory back-up
- Security systems
- Tracking systems
- Industrial applications

Electrical Specifications

(23±2°C)

Nominal capacity (4mA~2V):	0.75Ah
Rated voltage:	3.6V
Max constant current of discharge:	120mA
Max discharge current(pulse):	250mA
Operating temperature range:	-55°C ~ +85°C

 U.L. Component Recognition MH 49177

Physical Specifications

Diameter(max.)	14.5mm
Height(max.)	25.2mm
Weight(max.)	11g

Available terminations

S:Standard termination

T:Solder tabs


P:Axial pins

Special terminations are available upon request.

MSDS is available upon request.

TITUS LITHIUM BATTERY

ER14250M




S: Standard termination


Warning

- Fire, explosion and burn hazard
- Do not recharge, short circuit, crush, disassemble, heat above 100°C, incinerate
- Do not use the battery beyond the permitted temperature range

Discharge Characteristics at 23±2°C



Capacity VS. Current



Voltage VS. Temperature

